

**4T/5T Binary Tuning Switch,  $R_{ON}=0.5\Omega$ ,  $V=100V$**

**Features**

- Full integrated solution, single  $V_{DD}=2.6...5.25V$
- Frequency Range 30 MHz to 1000 MHz
- $R_{ON} = 0.5\Omega$
- 50 W CW Power
- $V_{PEAK} = 100V$
- Highest pulse power in the industry
- No sudden voltage breakdown compared to SOI
- Switch time =  $7.2\mu s$ , no power derating
- Low power consumption, less than 1 mW
- No need to supply negative voltages




Figure 1: TS63560D in  $6.0 \times 3.0\text{ mm}^2$  QFN 32-pin package.

**Applications**

- Tactical radio
- Tunable filters
- Antenna tuning
- Medical - Ultrasound
- Medical - MRI

**General Description**

The TS63560D is a HF/VHF/UHF/L-band fully integrated 4/5 throw tuning switch designed for high power tunable antenna and filter applications based on GaN technology. The TS63560D supports applications spanning 30 MHz through 1 GHz, providing low  $R_{ON}$  and high linearity within a small package size. The TS63560D is a 50 W CW with peak voltage capability of 100 V, switch suitable for applications requiring low insertion loss, high isolation, and high linearity. TS63560D utilizes standard single  $V_{DD}$ , no extra negative voltage needed, neither high voltages.

The TS63560D is packaged into a compact Quad Flat No lead (QFN)  $6.0 \times 3.0\text{ mm}^2$  32 leads plastic package.




Figure 2: TS63560D functional diagram



RoHS/Reach/Halogen free

## Absolute Maximum Ratings

Table 1: Absolute Maximum Ratings  $T_A = +25^\circ\text{C}$  unless otherwise specified<sup>1</sup>.

Parameter	Symbol	Value	Unit
<b>Electrical Ratings</b>			
Power Supply Voltage	$V_{DD}$	5.5	V
Storage Temperature Range	$T_{st}$	-55...+125	$^\circ\text{C}$
Operating Temperature Range	$T_{op}$	-40...+85	$^\circ\text{C}$
Maximum Junction Temperature	$T_j$	+140	$^\circ\text{C}$
Maximum RF CW input power	RFxI/RFxO	49	dBm
Maximum RF peak input power, 1% duty cycle, 10 $\mu\text{s}$ pulse	RFxI/RFxO	tbd	dBm
Maximum RF peak voltage	RFxI/RFxO	110	V
<b>Thermal Ratings</b>			
Thermal Resistance (junction-to-case) – Bottom side	$R_{\theta jc}$	tbd	$^\circ\text{C}/\text{W}$
Thermal Resistance (junction-to-top)	$R_{\theta jt}$	tbd	$^\circ\text{C}/\text{W}$
Soldering Temperature	$T_{solder}$	+260	$^\circ\text{C}$
<b>ESD Ratings</b>			
Human Body Model (HBM)	Level 1B	500...<1000	V
Charged Device Model (CDM)	Level C3	$\geq 1000$	V
<b>Moisture Rating</b>			
Moisture Sensitivity Level	MSL	1	

<sup>1</sup> Maximum ratings are absolute ratings. Exposure to absolute maximum rating conditions for extended periods may affect device reliability and can cause permanent damage to the device. Exceeding one or a combination of the absolute maximum ratings may cause permanent and irreversible damage to the device and/or to surrounding circuit. Functional operation of the device is not implied in any conditions above those indicated in the Electrical Specifications section.

## Electrical Specifications

 Table 2: Electrical Specifications  $T_A = +25^\circ\text{C}$ ;  $V_{DD} = +3.3\text{V}$ ;  $50\Omega$  Source/Load.

Parameter	Condition	Minimum	Typical	Maximum	Unit
Operating frequency	$f$	30		1000	MHz
RF1, RF2, RF3, ON Resistance	$R_{ON}$		0.50		$\Omega$
RF1, RF2, RF3, OFF Capacitance	$C_{OFF}$		500		fF
RF4, ON Resistance	$R_{ON}$		1.0		$\Omega$
RF4, OFF Capacitance	$C_{OFF}$		250		fF
RF5, ON Resistance	$R_{ON}$		2.0		$\Omega$
RF5, OFF Capacitance	$C_{OFF}$		125		fF
Insertion loss	50 MHz		0.08		dB
	500 MHz		0.10		dB
	1000 MHz		0.13		dB
RF1I – RF10, RF2I – RF20, RF3I – RF30	50 MHz		0.12		dB
	500 MHz		0.16		dB
	1000 MHz		0.20		dB
Insertion loss	50 MHz		0.25		dB
	500 MHz		0.30		dB
	1000 MHz		0.32		dB
RF5I – RF50	50 MHz		36		dB
	500 MHz		17		dB
	1000 MHz		11		dB
Isolation	50 MHz		44		dB
	500 MHz		24		dB
	1000 MHz		18		dB
RF4I – RF40	50 MHz		49		dB
	500 MHz		29		dB
	1000 MHz		24		dB
Isolation	50 MHz		-42		dB
	500 MHz		-37		dB
	1000 MHz		-36		dB
Return Loss	50 MHz		-36		dB
	500 MHz		-29		dB
	1000 MHz		-27		dB
RF4I – RF40	50 MHz		-31		dB
	500 MHz		-24		dB
	1000 MHz		-23		dB
Return Loss	50 MHz		-31		dB
	500 MHz		-24		dB
	1000 MHz		-23		dB
RF5I – RF50	50 MHz		-31		dB
	500 MHz		-24		dB
	1000 MHz		-23		dB

Table 3: Electrical Specifications  $T_A = +25^\circ\text{C}$ ;  $V_{DD} = +3.3\text{V}$ ;  $50\Omega$  Source/Load.

Parameter	Condition	Minimum	Typical	Maximum	Unit
Operating frequency	$f$	30		1000	MHz
<b>Harmonic Distortion</b>					
$H_2$ RF1, RF2, RF3	800MHz, $P_{in} = 35\text{dBm}$		118		dBc
$H_3$ RF1, RF2, RF3	800MHz, $P_{in} = 35\text{dBm}$		110		dBc
IIP3 RF1, RF2, RF3	800MHz		75		dBm
<b>Power and Compression point</b>					
$P_{\text{maxCW}}$	Max RF CW Power		48		dBm
$P_{\text{maxpeak}}$	Max RF Peak Power 1% duty cycle		tbd		dBm
<b>Noise</b>					
CP switching noise	RBW=1kHz		-140		dBm
<b>Switching Time</b>					
$t_{\text{ON}}^1$ RF1, RF2, RF3	Switch ON time		7.6		$\mu\text{s}$
$t_{\text{OFF}}^1$ RF1, RF2, RF3	Switch OFF time		7.6		$\mu\text{s}$
$t_{\text{RISE}}$	Switch RISE time		tbd		$\mu\text{s}$
$t_{\text{FALL}}$	Switch FALL time		tbd		$\mu\text{s}$
$t_{\text{startup}}$ , $C_{\text{VCP}} = 1\text{nF}$	startup time		0.8		ms
<b>Power Supply, DC</b>					
Control voltage	Power Supply $V_{DD}$	2.6	3.3	5.25	V
	All control pins high, $V_{ih}$	1.0	3.3	5.25	V
	All control pins low, $V_{il}$	-0.3	0	0.5	V
Control current	All control pins high, $I_{ih}$			7.5	$\mu\text{A}$
	All control pins low, $I_{il}$		0		$\mu\text{A}$
Current consumption	$I_{DD}$ , active mode ( $V_{DD}$ on)		220		$\mu\text{A}$

<sup>1</sup> This switching time is complete switching time. Many industry solutions require external biasing and control circuitry, which is not taken into account in switching time. TS63560D switching time definition includes time of the internal biasing and control circuitry.

## 4T Full Binary Weighted Application Example

TS63560D Tuning switch can be also used in fully binary configuration. This requires combined connection of RF1 and RF2 together, resulting  $R_{ON} = 0.25\Omega$ . This is helpful when designing tunable capacitor circuitry with constant Q. In case of series resonance circuitry, which is case here, Q can be written

$$Q = \frac{1}{\omega_0 RC} \tag{1}$$

Therefore to have constant Q tunable capacitor with binary weighted capacitance values, switch can be used as a 4T tuning switch with binary weighted series resistance. Assuming that  $C_1$  is largest capacitance, we can create for example following capacitor values

Table 4: Constant Q Example

RF Port	Capacitance $C$	Resistance $R$	$RC$ Product
RF1+RF2	16 pF	$0.25 \Omega$	4 pF $\Omega$
RF3	8 pF	$0.50 \Omega$	4 pF $\Omega$
RF4	4 pF	$1.00 \Omega$	4 pF $\Omega$
RF5	2 pF	$2.00 \Omega$	4 pF $\Omega$

With this example, one has 0 stage with small  $C_P$  capacitance and all values from 2 pF to 30 pF with the step size of 2 pF. Tagore is currently working to provide exact parameters, including minimum capacitance of  $C_P$ ,




Figure 3: TS63560D functional diagram in Full Binary Weighted 4T configuration.

## Legal Information

### Published by

TagoreTech Inc.  
601 Campus Drive, Suite C1  
Arlington Heights, IL 60004, USA  
©2024-2025 All Rights Reserved

### Legal Disclaimer

The information provided in this document shall in no event be regarded as a guarantee of conditions or characteristics. TagoreTech assumes no responsibility for the consequences of the use of this information, nor for any infringement of patents or of other rights of third parties which may result from the use of this information. No license is granted by implication or otherwise under any patent or patent rights of TagoreTech. The specifications mentioned in this document are subject to change without notice. Errors and omissions excepted.

### Sales Contact

Engineering samples available only thru TagoreTech sales, please contact: [support@tagoretech.com](mailto:support@tagoretech.com).

### TS63560D Product Page

Please visit TS63560D product page for further information [TS63560D Product Page](#)

### Latest datasheet of TS63560D

Latest version of TS63560D product brief is available for download: [TS63560D Product Brief](#)  
[TS63560D Datasheet](#) Link will work once datasheet published.

### TagoreTech Inc. Product Brochure and datasheets

Tagore Product Brochure and links to all available datasheets is available for download  
[TagoreTech Product Brochure](#)

### Changelog

Table 5: Changelog

Date	Revision	Notes
09/20/2025	0.1	Product Brief Published